

11

**DISCLAIMER** 

## **WCDA**

Construction Department Casper WY 82609 307.265.0603

## Specs By Location

Address: 1822 S Jefferson Casper (revised) Unit: Unit 01 Approx. Wall SF: 0 Ceiling/Floor SF: 0 Location: 1 - General Requirements Units **Unit Price Total Price** Spec # Spec Quantity Trade: **General Requirements** 5.1 **OWNER SPECIFIED LIGHT FIXTURES** 1.00 FΑ Use the following light fixtures or prior approved equivalent: 4 Bulb Chandelier (Dining Room): Progress Lighting, P4326-09, Brushed Nickel Ceiling Mount (Bedroom/Other): Progress Lighting, P3476-09, Brushed Nickel 3 Bulb Hanging (Foyer): Progress Lighting, P3474-09, Brushed Nickel Ceiling Fan w/ light: Hunter, 23943, White Vanity Light (Bathroom): Progress Lighting, 2 light, P3028-09 5.2 **OWNER SPECIFIED MATERIALS** 1.00 GR Use the following materials or prior approved equivalent unless otherwise specified: Wall Paint: Behr premium plus Ivory Mist or have it matched. Trim & Door Paint: Bright White Carpet: Mohawk, Traffic Master, Style: Lamont II, Color: Spice Bark. Vinyl Flooring #1: Armstrong, Initiator, Ancient Slate -- Peacock 66205 Vinyl Flooring #2: Armstrong, Initiator, Darien -- Almond 66155 Counter top: Formica, Venetian Gold, 6223-RW Cabinets: American Classics, Style: Hampton, Color: Cognac or Sandalwood Appliances: All appliances and electrical cover plates to be white unless noted otherwise. Ceramic Floor Tile: 12" x 12" DalTile, Series: Salerno, Color: Marrone Chiaro Ceramic Wall Tile: 6" x 6" DalTile, Series: Salerno, Color: Marrone Chiaro Hardware: All door hardware to be brushed nickel including hinges and stops.

1.00

GR

Wyoming Community Development Authority (WCDA) has completed a visual inspection of the property only. Use of this information is at your own risk. WCDA will not be held liable for any errors or omissions contained in the content of any inspection reports. The inspection is a visual inspection only to determine safety and health issues, visible essential repairs, visible system deficiencies, and repairs needed to preserve and protect the property. The inspection report is provided "as is" and WCDA expressly disclaims any and all warranties, express or implied, including but not limited to, any warranties of accuracy, reliability, title, merchant ability, non-infringement. fitness for a particular purpose or any other warranty, condition, guarantee or representation, whether verbal, in writing or in electronic form, including but not limited to the accuracy or completeness of any information contained therein or provided by inspection. In no event shall WCDA be liable for any special, indirect, or consequential damages or any damages

Add	ress: 182	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Loca	tion:	1 - General Requirements	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
	Spec#	Spec		Quantity	Units	Unit Price	Total Price
Trade	: 1	General Requirements					
		whatsoever resulting from loss of use, data or profits, whetle in an action of contract, negligence or other tortuous action arising out of or in connection with the use or performance information available from the inspection.	,				
4	14	CONTRACTOR ACCEPTS SCOPE OF WORK  The undersigned contractor certifies that he/she has carefu reviewed & agrees to perform the work described in this Work Write Up (WWU) with the "Date Inspected" date of & referred to as Exhibit 1. The contractor sha initial & date each page of the WWU.  X	ork	1.00	DU		
5	24	MANUFACTURER'S SPECS PREVAIL		1.00	GR		
3	24	All materials shall be installed in full accordance with the manufacturer's specifications for working conditions, surfactor preparation, methods, protection and testing.	e	1.00	GK		
6	31	CONSTRUCTION DEFINITIONS		1.00	GR		
		"Install" means to purchase, set up, test and warrant a new component. "Replace" means to remove and dispose of original material, purchase new material, deliver, install, tes and warrant. "Repair" means to return a building componer like new condition through replacement, adjustment and recoating of parts. "Reinstall" means to remove, clean, stor and install a component.	t it to				
7	35	VERIFY QUANTITIES/MEASUREMENTS  All Quantities stated in the attached specifications for this address using Units of Measure other than Each (EA), Roo (RM) or Dwelling Unit (DU) (e.g. SF of Drywall) are for the contractor's convenience and must be verified by the contract at a mandatory site inspection prior to bid submission. All quantities stated in the Units of Measure Each (EA), Room (RM) or Dwelling Unit (DU) are as stated. Discrepancies in Quantities found by the contractor must be communicated the Housing Rehabilitation Specialist prior to the submission a bid. Claims for additional funds due to discrepancies in Quantities shall not be honored if submitted after the bid submission.	actor	1.00	GR		
8	36	BUILDING PERMIT REQUIRED  If required by the Jurisdiction Having Authority, the contract responsible for submitting this owner-prepared work write up the building department, applying for, paying for and receive building permit prior to starting any work.	p to	1.00	EA		
9	42	CERTIFICATE OF OCCUPANCY  Prior to final payment, the contractor shall comply with and complete all items necessary to receive a Certificate of Occupancy or Certificate of Completion for the individual dwelling unit from the local municipality or county.		1.00	EA		
10	45	CONTRACTOR PRE-BID SITE VISIT  The contractor must inspect the property. Submission of a list presumptive evidence that the bidder has thoroughly examined the site and is conversant with the requirements		1.00	DU		

Addre	ess: 182	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	1 - General Requirements	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	1	General Requirements					
		the local jurisdiction.					_
11	51	INSURANCE REQUIREMENTS  The Contractor shall purchase, maintain & provide the Conspecialist with certificates of insurance for: Statutory Worke Comp and Employers Liability; Comprehensive General Liability Insurance with minimum bodily injury limits of \$100 per accident and \$300,000 per aggregate; Property Insurar upon the entire work at the site to the full insurance value thereof. The above policies shall name the Owner as insurbeneficiary.	er's ,000 ace	1.00	EA		
12	55	WORK TIMES  Contractors and their Subcontractors shall schedule workin hours between 8:00am and 6:00pm Monday through Friday Requests to work on weekends and before or after these homes to approved by the homeowner.	<i>'</i> .	1.00	GR		
13	77	NEW MATERIALS REQUIRED  All materials used in connection with this work write-up are be new, of first quality and without defects - unless stated otherwise or pre-approved by WCDA and Construction Specialist.	to	1.00	GR		
14	86	HOLD HARMLESS  The contractor will defend, indemnify and hold harmless the Agency, its officers and employees from liability and claim f damages or loss and expenses arising from the contractor's operations under this contract.	or	1.00	GR		
15	90	1 YEAR GENERAL WARRANTY  Contractor shall remedy any defect due to faulty material or workmanship and pay for all damage to other work resulting therefrom, which appear within one year from final payment Further, contractor shall furnish owner with all manufacture and suppliers' written warranties covering items furnished under this contract prior to release of the final payment.	g t.	1.00	DU		
16	120	FINAL CLEAN  Remove from site all construction materials, tools and debr Sweep clean all exterior work areas. Clean all interior work areas, removing all visible dust, stains, labels and tags. Wa all walls and interior components. Remove all blinds. Clear forced air ductwork if present. Clean all windows, vacuum a mop all floors, and include all other necessary cleaning actito provide a move-in ready, finished product.	sh all and	1.00	EA		
17	2031	RADON EVALUATION  Conduct an EPA approved sampling for Radon gas in the home. Provide a report. Complete this prior to the star of an other work.	ny	1.00	EA		
18	6712	SEWERSCOPE Scope and record sewer line condition and provide a writter condition report and video documentation to WCDA (tape, or flash drive.)		1.00	EA		

Addr	ess: 18	322 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	1 - General Requirements	Approx.	. Wall SF: 0		Ceiling/Floor SF:	0
S	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	9	Environmental Rehab					
19	2071	ASBESTOSACM ABATEMENT Remove and dispose of asbestos containing material (ACM) following all federal, state, and local laws. Utilize persons properly trained in accordance with the rules.		1.00	EA		
20	9003	LEAD-SPECIFIC LAWS, RULES, REGULATIONS & GUIDELINES  The execution of this work shall comply with all applicable federal, state and local laws, rules, regulations and guideline for lead dust environments, including but not limited to: 29 C 1926.62 - Lead Construction Standard; 29 CFR1910.1200 - Hazard Communication Standard; 40 CFR Part 745 - Lead-Based Paint Poisoning Prevention in Certain Residenti Structures (EPA Regulations); 24 CFR Part 35 - HUD's Lead Safe Housing Rule.	FR al	1.00	GR		
21	9023	CLEARANCE EXAMINATION  Using a trained and certified lead paint inspector, a lead haz risk assessor, or if approved, a sampling technician, one hot after completion of all lead hazard reduction, renovation and maintenance work, conduct a visual assessment for evidence of remaining paint chips, visible dust debris and residue. Randomly select four (4) floors, two (2) window sills and two window troughs to dust wipe test as per protocol in the HUD Guidelines. Submit the dust samples, plus a blank sample, that an EPA-accredited lead analytical laboratory for determination of lead content. Provide the owne, occupants and this agent with the clearance report and a "Notice of Lead Hazard Reduction" within 15 days of achieving final clearance, in accordance with 23 CFR Part 35.  LEAD WASTE DISPOSAL  Wet mist and wrap all architectural components in polyethyles.	e (2) o n cy	1.00	EA		
Trade:	10	sheeting to prevent dust release during transport. Separate Category I lead waste (paint chips, stripping sludge, HEPA debris and water filtrate) and non-hazardous waste. Ensure that all waste, both hazardous and non-hazardous, is managin accordance with state regulations.  Carpentry					
23	Custom			1.00	DU		
		Door hardware for any doors not specifically called out for replacement is to be replaced with brushed nickel hardware, including hinges, to provide a consistent appearance throughout the home.					
Trade:	22	Plumbing					
24	6610	WATER SUPPLYINSPECT,REPAIR Restore water service to structure. Conduct water pressure t as necessary to identify defects and leaks and make repairs bring structure into compliance with the current national and local plumbing code.		1.00	EA		
25	6705	WASTE LINESINSPECT, REPAIR		1.00	EA		

Addre	ess: 18	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	1 - General Requirements	Approx	. Wall SF: 0		Ceiling/Floor SF:	0
S	pec#	Spec		Quantity	Units	Unit Price	Total Pric
Trade:	22	Plumbing					
		Test waste lines for leaks and proper venting. Identify defect and make repairs to bring structure into compliance with the current plumbing code. Power snake drain to clear lines for fixtures to main street sewer.	ts				
Trade:	23	Electric					
26	7435	COMPLETE REWIRE  Remove all existing electrical wiring and outlets. Furnish and install all new code compliant components. Include hardwire with battery backup smoke detectors, per code requirement. Include all GFCI's in wet areas, per code. Include all AFCIs a breaker box as needed. Outlet, switches, and plates shall be white.  Place GFCI sticker on GFCI outlets with dual purpose breakers.  All permitting and associated fees, as well as additional code.	d at	1.00	EA		
		requirements, to be paid by contractor.	•				
27	7475	ELECTRIC SERVICE200 AMP  Replace existing electrical service with a residential, 200 am service, main disconnect, 110/220 volt, 24 circuit panel board meter socket, weather head, service cable, and ground rod a cable. Seal exterior service penetrations to maintain a waterproof building envelope.	d,	1.00	EA		
Trade:	24	Extermination					
28	8303	INSPECT & PROVIDE TERMITE REPORT Inspect and provide termite report for the property prior to the start of any other work.	Э	1.00	DU		
				L	ocation	Total:	
Locat	ion:	2 - Exterior	Approx.	. Wall SF: 0		Ceiling/Floor SF:	0
S	pec#	Spec		Quantity	Units	Unit Price	Total Pric
Trade:	2	Owner Participation					
29	210	OWNER TO REMOVE JUNK/DEBRIS  Remove all junk, trash and debris from the yard prior to construction and maintain the yard free of such debris follow construction. Include the removal of cinder blocks stockpiled West end of yard, removal of steel basketball post and remo of grill/smoker from backyard.	l in	1.00	EA		
Trade:	4	Site Work					
30	315	FENCECHAIN LINK 4' HIGH Scrape, wire brush existing steel fence rails. Paint rails to match existing color.		1.00	EA		

Addr	ess: 182	2 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	2 - Exterior	Approx.	. Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	4	Site Work					
31	330	FENCESTOCKADE 6' HIGH Dispose of any existing fence. (Ensure that all waste, both hazardous and non- hazardous, is managed in accordance v state regulations. refer to General requirements spec 9147 LEAD WASTE DISPOSAL) Install a 6' high wood stockade fence. Use all preservative treated lumber, 4"x4" ground contact rated posts set at least 36" deep in 9" diameter concrete sleeves 8' on center. 2"x4" top, bottom, and middle rails, 1"x6" dog eared fence boards. Installation of sections shall be in a straight line unless otherwise stated.	vith	75.00	LF		
32	460	TRIM ALL OVERGROWTH  Trim all dead, decaying, damaged and overgrown plants, shrubs and trees, to provide safety and an attractive appearance. Remove 50% of tree limb length that overhang any structure. Remove all debris and rake clean.	s	1.00	EA		
33	465	REMOVE TREE AND GRIND STUMP  Cut and remove large cottonwood tree in yard to legal dump  Grind stump to 18" below grade. Install top soil and reseed a  disturbed areas.		1.00	EA		
34 Trade:	Custom 6	REPAIR/RESTORE LANDSCAPE RAIL TERRACE Repair and stabilize landscape terrace in backyard. Replace rails as needed.  Concrete & Paving	•	1.00	EA		
35	945	FLATWORKCUSTOM  Remove and replace concrete walkway extending from front deck to rear entry along South side of home. Assure proper cross-slope to drain water away from foundation. Coordinate with installation of basement egress window and window well	)	1.00	EA		
Trade:	7	Masonry					
36	1155	FOUNDATIONCUSTOM MASONRY Fill with concrete epoxy, any cracks between house and foundation and any cracks greater than 1/4" on flatwork arou house	nd	1.00	EA		
Trade:	10	Carpentry					
37	2330	DECKINGCUSTOM  Replace existing wood steps on both ends of front deck, firm anchoring steps to slab. Scrape, sand, and prep deck, rails and other components to receive two coats Behr Premium deck paint or approved equal. approved by WCDA construct specialist.		1.00	EA		
38	2640	SIDINGVINYL Hang Alside Conquest vinyl clapboard siding including all cornice, corner, soffit, door and window trim after replacing a deteriorated exterior building components. Wrap home with tyvek vapor/ infiltration barrier and apply owner's choice of	II	1.00	EA		

Addr	ess:	1822 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	2 - Exterior	Approx	. Wall SF: 0		Ceiling/Floor SF:	0
s	pec #	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	) Carpentry					
		siding color, exposure and texture with 50 year warrant; Prior to installing siding, remove all existing stucco finis exterior of house and garage, dispose of properly and sheathing.	h from				
39	2835	WINDOW WELL Using a shovel, excavate area directly adjacent to base window within 4" of desired depth. Place corrugated galvanized 37" wide x 24" deep window well into ground press against foundation. Fill excavated area up to win with landscaping rock. Place and tamp extra soil again exterior of well. Provide clear window well covers for two non-egress basement windows.	d and dow sill st	2.00	EA		
Trade:	1	5 Roofing					
40	4635	GUTTER5" SEAMLESS ALUMINUM  Dispose of gutter. Install 5", K- type, seamless, .027 ga aluminum gutter to service roof. Color:White Include all necessary downspouts and extensions or splashblocks to assure drainage water is moved away f house foundation.		150.00	LF		
41	4635	GUTTER5" SEAMLESS ALUMINUM  Dispose of gutter. Install 5", K- type, seamless, .027 ga aluminum gutter to service roof. Color: White. Include all necessary downspouts and extensions or splashblocks to assure drainage water is moved away f house foundation.		150.00	LF		
Trade:	2	2 Plumbing					
42	7135	HOSE BIBB Install a bronze, freeze free hose bibb on outside of struwith inside shut-off valve and backflow preventer. Seal penetration with silicone caulk.		2.00	EA		
		On East side and West side of house. Coordinate with construction specialist for exact location.	WCDA				
43	7255	LAWN SPRINKLER SYSTEM Install an underground piped irrigation system with a 1" filter, back flow preventer, polybutylene supply, sufficiento provide overlapping irrigation to entire lawn area, and	nt heads	1.00	EA		
Trade:	2	B Electric					
44	8160	ENTRANCE LIGHT  Install an exterior, waterproof, wall mounted, single bulk outside exterior doors of house. Include wire box, interior switch and lamp. Fish wire and repair all tear out. Fixtuallowance \$22.	or	2.00	EA		
45	8162	ENTRANCE LIGHTENERGY STAR Install an Hampton Bay 180-Degree Outdoor Motion-Se Wall Lantern Model # HB48017MP-237 - ENERGY STA	•	2.00	EA		

Address: 182	22 S Jefferson Casper (revised)	Unit: L	Jnit 01			
Location:	2 - Exterior	Approx. W	all SF: 0		Ceiling/Floor SF:	0
Spec #	Spec		Quantity	Units	Unit Price	Total Price
Trade: 23	Electric					
	rated, exterior, wall mounted, single bulb fixture with both a dusk to dawn sensor and a motion detector. Include wire box interior switch and lamp. Fish wire and repair all tear out.  TO BE INSTALLED ABOVE GARAGE MAN DOOR AND ABOVE GARAGE OVERHEAD DOOR IN ALLEY.	Κ,	L	ocation	Total:	
Location:	3 - Entry/Mud Room	Approx. W	all SF: 0		Ceiling/Floor SF:	0
Spec #	Spec		Quantity	Units	Unit Price	Total Price
Trade: 10	Carpentry					
46 <b>2980</b>	WINDOWVINYL DBL HNG DBL GLZ Field measure, order and install a vinyl, double hung, double glazed, one-over-one window and jamb including screen, ca interior casing and exterior trim. Install half screen.		3.00	EA		
47 3210	STORM DOORALUMINUM Install an aluminum storm door with 3/4 glass and white bake enamel aluminum finish.	ed	1.00	EA		
Trade: 19	Paint & Wallpaper					
48 5565	PREP & PAINT VACANT ROOM  Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surface with TSP. Spot prime and top coat trim, ceiling, walls, doors windows with owner's choice of premixed acrylic latex. Including any closets, rooms, walls, ceiling and trim.	ces &	75.00	SF		
Trade: 20	Floor Coverings					
49 <b>5995</b>	CARPETCUSTOM  Provide new indoor/outdoor carpet after properly prepping surface and sealing any openings in floor or between floor at house.	nd	1.00	EA		
Trade: 23	Electric					
50 <b>7730</b>	LIGHT FIXTUREREPLACE		1.00	EA		
	Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with sharor globe and lamps.		Lo	ocation	Total:	
Laggian	4 Living Poom	Approx. W	all SE: 0		Ceiling/Floor SF:	0
Location:	•	Approx. W		11		
Spec #	Spec		Quantity	Units	Unit Price	Total Price

Addre	ess: 18	322 S Jefferson Casper (revised)	Unit:	Unit 01			
Locati	on:	4 - Living Room	Approx.	. Wall SF: 0		Ceiling/Floor SF:	0
Sı	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
51	2979	VINYL SLIDING DOUBLE GLAZED WINDOW  Remove existing window, field measure, fabricate and instal dual glazed, thermal break, vinyl sliding window including all paint, caulk, trim, and provide a screen. Use privacy glazing bathroom windows. Clean the glass when complete.		1.00	EA		
52	2980	WINDOWVINYL DBL HNG DBL GLZ		2.00	EA		
		Field measure, order and install a vinyl, double hung, double glazed, one-over-one window and jamb including screen, ca interior casing and exterior trim. Install half screen.					
53	3175	DOORENTRY COMPLETE  Dispose of existing door and frame. Install a 1-3/4" six-pane fiberglass door and frame. Include interior and exterior casin three 4"x 4" butt hinges, spring metal weatherstripping, an interlocking threshold, 1/4 glass, one entrance and one mortised deadbolt lockset keyed alike. Prime and topcoat w owner's choice of finish.	g,	1.00	EA		
Trade:	18	Ceramic Tile					
54	5425	CERAMIC FLOOR TILE		24.00	SF		
Trade:	19	Remove and replace tile flooring at entry with porcelain tile.  Paint & Wallpaper					
55	5565	PREP & PAINT VACANT ROOM		300.00	SF		
		Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surface with TSP. Spot prime and top coat trim, ceiling, walls, doors windows with owner's choice of premixed acrylic latex. Including lossets, rooms, walls, ceiling and trim.	&	000.00	G.		
Trade:	20	Floor Coverings					
56	5970	CARPET AND PAD Install FHA approved, nylon, plush carpet over a 1/2" mediur density rebond pad w/ a minimum of seams. Stretch carpet t eliminate puckers, scallops & ripples. Include tackless strips metal edge strips, and mending tape to cover entire floor including closets. On stairs, fasten carpet and pad at top and bottom of each riser. See General Requirements for specific carpet.	0	300.00	SF		
Trade:	23	Electric					
57	7730	LIGHT FIXTUREREPLACE  Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with sharor globe and lamps.	de	1.00	EA		
				L	ocation	Total:	

Addr	ess: 18	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	5 - Kitchen A	pprox.	Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
58	2980	WINDOWVINYL DBL HNG DBL GLZ Field measure, order and install a vinyl, double hung, double glazed, one-over-one window and jamb including screen, cau interior casing and exterior trim. Install half screen.	lk,	1.00	EA		
59	3705	CABINETSREPAIR  Repair base and hanging cabinets by rehanging plumb and level and replacing missing hardware, doors and drawers. Securely refasten loose hardware. Clean all surfaces with detergent.  Firmly secure countertop at pass-thru to Living Room.		1.00	EA		
Trade:	19	Paint & Wallpaper					
60	5555	PREP/PAINT KITCHENSEMI GLOSS Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces w/sandpaper. Clean all surfaces with TSP. Fill all holes/cracks. Spot prime with acrylic latex. Apply top coat of owner's choice of premixed acrylic latex semi-gloss. Include any closets.		1.00	RM		
Trade:	20	Floor Coverings					
61	5920	UNDERLAY AND VINYL COMPOSITION TILE Install 1/4" underlayment grade plywood using 7d screw shan or cement coated nails, or narrow crown staples, 6" on center allowing a 1/4" gap at wall. Fill seams with a manufacturer approved filler. Lay 12"x12"x1/8" vinyl composition tile, color group B as made by Armstrong or Azrock, per manufacturer's recommendations. Square to room axis. Include metal edge strips at openings,and shoe molding or 4" vinyl base around perimeter.Owner's choice of in-stock color.		175.00	SF		
Trade:	22	Plumbing					
62	6810	<b>FAUCETKITCHEN SINGLE LEVER2.0 GPM</b> Install a single lever, washerless, metal bodied faucet with 15 year drip-free guarantee and maximum flow of 2 gallons per minute.		1.00	EA		
Trade:	23	Electric					
63	7730	<b>LIGHT FIXTUREREPLACE</b> Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with shad or globe and lamps.	e	2.00	EA		
Trade:	25	Appliances					
64	8415	GAS STOVE30" Dispose of old stove. Install a white, 30" wide, pilotless, gas		1.00	EA		

Addr	ess: 18	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Loca	tion:	5 - Kitchen	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
	Spec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	25	Appliances					
		stove including gas oven and electrical connections.					
65	8450	MICROWAVE Dispose of microwave oven. Provide 1000 watt, 1.7 cu ft Microwave Oven with integral turn table. Product to be Own specified GE Appliances model #JVM1740DMWW or prior approved equivalent. Color to be selected by owner.	er	1.00	EA		
66	8475	REFRIGERATOR18 CFENERGY STAR Dispose of old refrigerator. Install an ENERGY STAR approved 2 door, top freezer, frost free refrigerator with at lea 17.5 cubic feet. Color to be selected by owner.	ast	1.00	EA		
67	8491	DISHWASHER2 CYCLEENERGY STAR  Provide and install a 24", 2 cycle (minimum), built-in Energy Star® labeled dishwasher including all alterations and connections to plumbing and electric system Frigidaire, Model# FBD2400KW - or - GE Model# GSD2100VWW. Cold to be selected by owner.	or	1.00	EA		
68	8500	DISPOSAL1/2 HP Install a 1/2 horsepower, PVC chambered, quick disconnect, garbage disposal with reset button and hand crank, as manufactured by ISE, model Badger 333. Include plumbing and electrical connections.		1.00	EA		
				L	ocation	Total:	

Locat	tion:	6 - Rear Entry/Stair	Approx. Wall	SF: 0		Ceiling/Floor SF:	0
S	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
69	2520	HANDRAILREPLACE INTERIOR Install 2" round hardwood handrail screwed to metal handrail braces that are attached to studs with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners ar compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.		12.00	LF		
70	3175	DOOR-ENTRY COMPLETE Dispose of existing door and frame. Install a 1-3/4" six-panel fiberglass door and frame. Include interior and exterior casing three 4"x 4" butt hinges, spring metal weatherstripping, an interlocking threshold, 1/4 glass, one entrance and one mortised deadbolt lockset keyed alike. Prime and topcoat wit owner's choice of finish.	J,	1.00	EA		
71	3210	STORM DOORALUMINUM Install an aluminum storm door with 3/4 glass and white bake enamel aluminum finish.	d	1.00	EA		

Addre	ess: 18	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Locati	ion:	6 - Rear Entry/Stair	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
Sı	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	17	Drywall & Plaster					
	5270	DRYWALL1/2"  Hang, tape and 3 coat finish 1/2" drywall. Apply a 3/8" bead low VOC drywall adhesive to each framing member and insusing drywall screws min. 1 5/8 long, 8"on center. Run boa with long dimension perpendicular to framing members. Sa ready for paint.  Construct soffit to conceal vent pipe exposed in corner of st	tall rds nd	220.00	SF		
		Include repair of ceiling. TO INCLUDE FURRING STRIPS FOR GYP BOARD ON FOUNDATION WALL					
Trade:	18	Ceramic Tile					
73	5425	CERAMIC FLOOR TILE  Remove and replace entry tile.		24.00	SF		
Trade:	19	Paint & Wallpaper					
74	5565	PREP & PAINT VACANT ROOM  Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surfa with TSP. Spot prime and top coat trim, ceiling, walls, doors windows with owner's choice of premixed acrylic latex. Incluany closets, rooms, walls, ceiling and trim.	ices s &	100.00	SF		
Trade:	20	Floor Coverings					
75	5970	CARPET AND PAD Install FHA approved, nylon, plush carpet over a 1/2" mediu density rebond pad w/ a minimum of seams. Stretch carpet eliminate puckers, scallops & ripples. Include tackless strips metal edge strips, and mending tape to cover entire floor including closets. On stairs, fasten carpet and pad at top an bottom of each riser. See General Requirements for specific carpet.	to s, d	150.00	SF		
Trade:	23	Electric					
<b>7</b> 6	7730	LIGHT FIXTUREREPLACE  Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with sha or globe and lamps.		1.00	EA		
				Lo	ocation	Total:	
Locati	ion:	7 - Family Room	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
Sı	pec#	Spec		Quantity	Units	Unit Price	Total Price
	10	Carpentry					

Addre	ess: 182	2 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	7 - Family Room	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
77	2979	VINYL SLIDING DOUBLE GLAZED WINDOW  Remove existing window, field measure, fabricate and insta dual glazed, thermal break, vinyl sliding window including all paint, caulk, trim, and provide a screen. Use privacy glazing bathroom windows. Clean the glass when complete.	I	3.00	EA		
78	2980	WINDOWVINYL DBL HNG DBL GLZ Field measure, order and install a vinyl, double hung, doubl glazed, one-over-one window and jamb including screen, ca interior casing and exterior trim. Install half screen.		3.00	EA		
Trade:	17	Drywall & Plaster					
79	5270	DRYWALL1/2" Remove existing paneling. Hang, tape and 3 coat finish 1/2 drywall. Apply a 3/8" bead of low VOC drywall adhesive to 6 framing member and install using drywall screws min. 1 5/8 long, 8"on center. Run boards with long dimension perpendicular to framing members. Sand, match existing texture, ready for paint.		300.00	SF		
80	Custom	CEILING REPAIR & TEXTURE  Repair any and all damaged areas in the ceiling and retextuto provide a consistent finish and appearance.	re	1.00	EA		
Trade:	19	Paint & Wallpaper					
81	5565	PREP & PAINT VACANT ROOM  Remove/cover all hardware, fixtures not to be painted. We scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surfa with TSP. Spot prime and top coat trim, ceiling, walls, doors windows with owner's choice of premixed acrylic latex. Incluany closets, rooms, walls, ceiling and trim.	ices s &	300.00	SF		
Trade:	20	Floor Coverings					
82	5970	CARPET AND PAD Install FHA approved, nylon, plush carpet over a 1/2" mediudensity rebond pad w/ a minimum of seams. Stretch carpet eliminate puckers, scallops & ripples. Include tackless strips metal edge strips, and mending tape to cover entire floor including closets. On stairs, fasten carpet and pad at top an bottom of each riser. See General Requirements for specific carpet.	to s, d	300.00	SF		
Trade:	23	Electric					
83	7730	LIGHT FIXTUREREPLACE  Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with sharor globe and lamps.		1.00	EA		

Address: 1822 S Jefferson Casper (revised) Unit: Unit 01

Location Total:

Locat	ion:	8 - Utility Room	Approx. Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec	Quantity	Units	Unit Price	Total Price
Trade:	5	Demolition & Disposal				
84	Custom	REMOVE WATER SOFTENER  Remove and dispose of water softener and all associated plumbing.	1.00	EA		
Trade:	10	Carpentry				
85	3260	REWORK INTERIOR DOOR/STORAGE ABOVE UTILITY  Adjust doors to operate properly. Replace hinges if necessar Replace opener hardware / match with kitchen.	1.00 ary.	EA		
86	3375	DOORWOOD BIFOLD  Hang a flush, hollow core, wood bifold door including overhetrack, all hardware and casing on one side, plumb and centered within the opening.	1.00 ad	EA		
87	Custom	<b>REMOVE CABINETS</b> Remove and properly dispose of existing cabinet uppers.	1.00	EA		
Trade:	19	Paint & Wallpaper				
88	5566	PREP & PAINT VACANT ROOM  Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surface with TSP. Spot prime and top coat trim, ceiling, walls, doors windows with owner's choice of premixed acrylic latex. Including any closets.	&	SF		
Trade:	20	Floor Coverings				
89	5930	UNDERLAYMENT AND VINYL SHEET GOODS Install 1/4" underlayment grade plywood using 7d screw sha or cement coated nails, or narrow crown coated staples, 6" of center allowing a 1/4" gap at wall. Fill seams with a manufacturer approved filler. Install 070" thick, backed vinyl sheet goods w/ minimum seams, per manufact. recommendations. Install metal edge strips in openings. Owner's choice of pattern and color.		SF		
Trade:	21	HVAC				
90	6040	FURNACE 90+ GAS - WITH DISTRIBUTION  Use the Air Conditioning Contractors of America's (ACCA) latest edition of their Manual J Heat loss calculation tool http://www.acca.org/tech/manualj/ (calculate manual J based on the post rehab building envelope), use ACCA's Manual S equipment selection and use Manual D for ductwork design. Make every effort to install supply ducts in interior partitions conditioned wall cavities). NOTE: Provide Manual J, S and I reports before work begins. Size furnace to the living unit considering any areas which may be added or subtracted from the plan. Remove existing furnace or boiler, recycle all metal.	for (in ) m	EA		

	tion:	8 - Utility Room	Approx.	. Wall SF: 0		Ceiling/Floor SF:	0
5	Spec #	Spec		Quantity	Units	Unit Price	Total Price
Γrade:	21	HVAC					
		components and dispose of all other materials in a code legal dump. FURNACE: install a 90+ gas fired forced air furnace with minimum AFUE rating of 90% or higher on 2" patio bloc to with new supply and return ductwork work & gas line. New furnace to be vented with PVC piping per manufacturer's specifications. New furnace will have minimum limited warranties of: 20 years on heat exchangers; 5 years on parts include auto set back thermostat controls, vent pipe & new shut-off valve. Install return air duct ensuring easy access, good fit & easy replacement of air filter. An exterior return air filter box shall be installed on one side, both sides, or bottom new furnace. Seal all duct joints with Duct Mastic.	ς , , ,				
1	6415	DRYER VENT		1.00	EA		
		Install 4" round rigid galvanized ductwork from the specified dryer location to a wall mounted Heartland Dryer Vent Closu outlet.  http://www.energyfederation.org/consumer/default.php/cPath 0_4287_4571. Do not fasten with nails, screws or other fasteners that protrude into the interior of the exhaust duct. Use pop rivets to connect sections of duct. Seal all joints an seams with duct mastic, not duct tape. Secure duct and hoo to framing.	n/3 d				
Trade:		Plumbing					
92	7070	WATER HEATER40 GALLON GAS Install a 40 gallon, glass lined, high recovery, insulated to R- gas water heater with a 10 year warranty. Include pressure and temperature relief valve, discharge tube to within 6" of floor to outside of structure, vent, thimble, and gas piping from shut-off valve to fixture. Dispose of old water heater in code legal dump.		1.00	EA		
93	7120	DRIPLESS CENTERWASHER HOOK UP		1.00	EA		
		Install PVC stand pipe, hot and cold hose bibbs, and 20 amp outlet on a separate circuit to service a washing machine. Remove drain plug at conclusion of construction and place tape over hole to protect opening.				_	
		REMOVE BOILER		1.00	EA		
94	Custom						
94	Custom	Remove boiler and all associated plumbing/exhaust. Remove all hydronic lines where feasible cap and abandon. Include removal of baseboard units from each room. Repair and pair to match existing as needed.					
)4 Frade:		all hydronic lines where feasible cap and abandon. Include removal of baseboard units from each room. Repair and pai					

Locati	ion:	9 - Hall	pprox.	Wall SF: 0		Ceiling/Floor SF:	0
S	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	19	Paint & Wallpaper					
96	5565	PREP & PAINT VACANT ROOM  Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surface with TSP. Spot prime and top coat trim, ceiling, walls, doors & windows with owner's choice of premixed acrylic latex. Include any closets, rooms, walls, ceiling and trim.	ι	30.00	SF		
Trade:	20	Floor Coverings					
97	5970	CARPET AND PAD Install FHA approved, nylon, plush carpet over a 1/2" medium density rebond pad w/ a minimum of seams. Stretch carpet to eliminate puckers, scallops & ripples. Include tackless strips, metal edge strips, and mending tape to cover entire floor including closets. On stairs, fasten carpet and pad at top and bottom of each riser. See General Requirements for specified carpet.		30.00	SF		
Trade:	23	Electric					
98	7740	LIGHT FIXTURE AND SWITCH Install a ceiling mounted, UL approved, 2 bulb light fixture (\$2 material allowance) controlled by a switch with cover plate located at the strike side of the door. Fish wire and repair all tear out.	)	1.00	EA		

			A W-II OF. O		0-:::/5105-	0
Locat	iion:	10 - Bathroom	Approx. Wall SF: 0		Ceiling/Floor SF:	U
s	pec#	Spec	Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry				
99	2980	WINDOWVINYL DBL HNG DBL GLZ Field measure, order and install a vinyl, double hung, double glazed, one-over-one window and jamb including screen, ca interior casing and exterior trim. Install half screen.		EA		
100	3825	MEDICINE CABINETSURF MOUNT 16X22 Install a 16"x22" metal, surface mounted medicine cabinet whinged plate glass mirror and two shelves.	1.00 vith	EA		
101	3835	ACCESSORY SET4 PIECE Install a brushed nickel or chrome bathroom accessory set consisting of two 20" - 24" towel bars, one towel ring, and a toilet paper holder.	1.00	EA		
Trade:	19	Paint & Wallpaper				
102	5560	PREP & PAINT BATHROOM  Remove/cover all hardware and fixtures not to be painted. Scrape all loose cracked, peeling blistered surfaces. Clean	1.00 Wet	RM		

Locati	ion:	10 - Bathroom A	pprox.	Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Гrade:	19	Paint & Wallpaper					
		surfaces with TSP. Fill all holes and cracks. Spot prime with acrylic latex. Apply top coat of owner's choice of premixed acrylic latex semi-gloss.					
rade:	20	Floor Coverings					
103	5930	UNDERLAYMENT AND VINYL SHEET GOODS Install 1/4" underlayment grade plywood using 7d screw shan or cement coated nails, or narrow crown coated staples, 6" or center allowing a 1/4" gap at wall. Fill seams with a manufacturer approved filler. Install 070" thick, backed vinyl sheet goods w/ minimum seams, per manufact. recommendations. Install metal edge strips in openings. Owner's choice of pattern and color.		75.00	SF		
Гrade:	22	Plumbing					
04	6870	FAUCETLAVATORY DUAL CONTROL		1.00	EA		
		Install a washerless, metal bodied, dual control faucet with a year drip-free warranty. Include shut-off valve. Replace trap required to complete installation.					
05	6930	TUB/SHOWER FAUCET WITH DIVERTER Install a single lever, metal shower diverter with faucet, controls, and shower head set (Glacier Bay Item # 418827 or equal) in brushed nickel or prior approved equivalent with 15 year drip-free warranty.		1.00	EA		
06	7010	COMMODEREPLACE Install a 2 piece, close coupled, white, vitreous china, commode with a maximum water usage per flush of 1.6 Gallons. Include white seat, supply pipe, shut-off valve, flap valve and wax seal.		1.00	EA		
Гrade:	23	Electric					
07	7731	LIGHT FIXTUREREPLACE VANITY  Replace light fixture with 2 or 3 bulb vanity light. Include shad and lamps. See General Conditions for specified material.	е	1.00	EA		
08	7818	FIXTURELIGHT, VENT Install a single bulb light fixture with an exterior ducted vent fa with damper capable of 60 cfm, controlled by 2 manufacturer-supplied switches, using #14 copper Romex. Fish all wire and repair tear out.	n	1.00	EA		
				L	ocation	Total:	
Locat	ion:	11 - Rear Bedroom A	pprox.	Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price

Addre	ess: 182	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	11 - Rear Bedroom	Approx.	. Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
109	2980	WINDOWVINYL DBL HNG DBL GLZ Field measure, order and install a vinyl, double hung, double glazed, one-over-one window and jamb including screen, ca interior casing and exterior trim. Install half screen.		2.00	EA		
		Note: West window to be egress compliant.					
110	3345	DOORINT, HOLLOW CORERAISED PANEL		1.00	EA		
		Install a raised panel, hollow core, masonite door on existing jamb. Include privacy lockset and 2 butt hinges.	I				
Trade:	17	Drywall & Plaster					
111	Custom	PARTITION CLOSET  Frame and finish with 1/2" gyp board a partition at midpoint of shared closets to provide two separate closets. Texture to match existing, ready to paint. Provide any trim necessary to provide consistent appearance. Remove existing shelving a replace with shelves and closet rods in both closets.	0	1.00	EA		
Trade:	19	Paint & Wallpaper					
112	5565	PREP & PAINT VACANT ROOM  Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surface with TSP. Spot prime and top coat trim, ceiling, walls, doors windows with owner's choice of premixed acrylic latex. Including any closets, rooms, walls, ceiling and trim.	ces &	300.00	SF		
Trade:	20	Floor Coverings					
113	5970	CARPET AND PAD Install FHA approved, nylon, plush carpet over a 1/2" mediur density rebond pad w/ a minimum of seams. Stretch carpet teliminate puckers, scallops & ripples. Include tackless strips metal edge strips, and mending tape to cover entire floor including closets. On stairs, fasten carpet and pad at top and bottom of each riser. See General Requirements for specific carpet.	o ,	200.00	SF		
Trade:	23	Electric					
114	7730	LIGHT FIXTUREREPLACE  Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with sharor globe and lamps.	de	1.00	EA		
				L	ocation	Total:	

Approx. Wall SF: 0

Location:

12 - Front Bedroom

Ceiling/Floor SF: 0

Addr	ess: 182	2 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	12 - Front Bedroom	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
115	2980	WINDOWVINYL DBL HNG DBL GLZ Field measure, order and install a vinyl, double hung, double glazed, one-over-one window and jamb including screen, ca interior casing and exterior trim. Install half screen. Window on East wall to be egress compliant.		2.00	EA		
116	3420	ATTIC ACCESS  Provide a hatch door of 1/2" plywood and attach 6" of foil factory polyiscocyanurate foam board with the edges of the foam board sealed with aluminum foil tape. Trim the opening with casing to match room using the casing to create a lip to supper the hatch door. Caulk all seams in the assembly with low VC caulk. Weatherstrip with adhesive faced foam weatherstripp tape on the top edge of the casing that supports the door to create an airtight seal.	oort OC	1.00	EA		
117	Custom	ADJUST CLOSET DOOR  Repair and adjust closet door to provide smooth, reliable operation.		1.00	EA		
Trade:	19	Paint & Wallpaper					
118	5565	PREP & PAINT VACANT ROOM  Remove/cover all hardware, fixtures not to be painted. Wet scrape loose, cracked, peeling, blistered surfaces. Feather edges & dull gloss surfaces with sandpaper. Clean all surface with TSP. Spot prime and top coat trim, ceiling, walls, doors windows with owner's choice of premixed acrylic latex. Including any closets, rooms, walls, ceiling and trim.	&	200.00	SF		
Trade:	23	Electric					
119	7730	LIGHT FIXTUREREPLACE  Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with shar or globe and lamps.	de	1.00	EA		
				Lo	ocation	Total:	
Locat	ion:	13 - Bsmnt Hall	Approx.	Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	5	Demolition & Disposal					
120	Custom	REMOVE FURNACE IN CRAWLSPACE.  Remove old furnace in crawl. Remove /cap all existing plumbing and supply/ air return lines.		1.00	EA		
Trade:	10	Carpentry					
121	3360	DOORPREHUNG PASSAGESPLIT JAMB Install a 1-3/8" prehung, flush, hollow core door and split jam including casing both sides, 2 butt hinges and a privacy lock		1.00	EA		

Addr	ess: 182	2 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	13 - Bsmnt Hall	Approx	. Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
		in new partition opening.					
122	Custom	CONSTRUCT DOORWAY  Frame and finish with 1/2" gyp board a partition at East end hall with rough door opening to bedroom.	d of	1.00	EA		
Trade:	16	Conservation					
123	4955	VAPOR BARRIERCRAWL SPACE		1.00	EA		
		Lay 6 mil poly vapor barrier on ground in crawl space and 6 foundation walls. Overlap seams by 2' and secure with ductape.					
Trade:	17	Drywall & Plaster					
124	5210	DRYWALLPATCHLARGE		1.00	EA		
		Cut back defective gypsum to expose half of the studs on a side of the hole. Cut and tightly fit drywall patch. Glue and or screw patch. Apply tape and 3 coats of compound feath out at least 8". Wet sand ready for paint.	l nail				
125	5270	DRYWALL1/2"		50.00	SF		
		Hang, tape and 3 coat finish 1/2" drywall. Apply a 3/8" bead low VOC drywall adhesive to each framing member and insusing drywall screws min. 1 5/8 long, 8"on center. Run bowith long dimension perpendicular to framing members. Scready for paint.  Fir out North wall to conceal plumbing.	stall ards				
Trade:	19	Paint & Wallpaper					
126	5565	PREP & PAINT VACANT ROOM		100.00	SF		
		Remove/cover all hardware, fixtures not to be painted. We scrape loose, cracked, peeling, blistered surfaces. Feathe edges & dull gloss surfaces with sandpaper. Clean all surf with TSP. Spot prime and top coat trim, ceiling, walls, doo windows with owner's choice of premixed acrylic latex. Incl any closets, rooms, walls, ceiling and trim.	r aces rs &				
Trade:	20	Floor Coverings					
127	5930	UNDERLAYMENT AND VINYL SHEET GOODS Install 1/4" underlayment grade plywood using 7d screw shor cement coated nails, or narrow crown coated staples, 6" center allowing a 1/4" gap at wall. Fill seams with a manufacturer approved filler. Install 070" thick, backed vin sheet goods w/ minimum seams, per manufact. recommendations. Install metal edge strips in openings. Owner's choice of pattern and color.  Provide rubber base trim.	on	50.00	SF		
Trade:	23	Electric					

Addr	ess: 18	22 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	13 - Bsmnt Hall	Approx.	Wall SF: 0		Ceiling/Floor SF	: 0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	23	Electric					
128	7730	LIGHT FIXTUREREPLACE Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with shor globe and lamps.	-	1.00	EA		

**Location Total:** 

Locat	ion:	14 - Bsmnt Bathroom	Approx. Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec	Quantity	Units	Unit Price	Total Price
Trade:	4	Site Work				
129	Custom	FILL IN SUMP WELL Remove existing sump pump and associated electrical connections from sump well in floor of bathroom. Fill in well with gravel and pour concrete to seal sump well. Finish surface smooth and level.	1.00	EA		
Trade:	10	Carpentry				
130	2981	VINYL WINDOW-BASEMENT Dispose of basement window unit. Install a vinyl slider window plumb and level, caulk, provide a screen.	1.00 bw,	EA		
131	3360	DOORPREHUNG PASSAGESPLIT JAMB Install a 1-3/8" prehung, flush, hollow core door and split jam including casing both sides, 2 butt hinges and a privacy locks		EA		
132	3680	TUB SURROUNDPREFAB Install a white fiberglass or acrylic, 3- or 5-piece, tub surroun kit with a built-in soap dish. Caulk all joints with white, milder resistant siliconized caulk. Prepare substrate and attach panels using manufacturer's recommended adhesive and fasteners.		EA		
133	3825	MEDICINE CABINETSURF MOUNT 16X22 Install a 16"x22" metal, surface mounted medicine cabinet w hinged plate glass mirror and two shelves.	1.00 ith	EA		
134	3835	ACCESSORY SET4 PIECE Install a brushed nickel or chrome bathroom accessory set consisting of two 20" - 24" towel bars, one towel ring, and a toilet paper holder.	1.00	EA		
Trade:	17	Drywall & Plaster				
135	5270	DRYWALL1/2" Hang, tape and 3 coat finish 1/2" drywall. Apply a 3/8" bead of low VOC drywall adhesive to each framing member and instrusing drywall screws min. 1 5/8 long, 8"on center. Run board with long dimension perpendicular to framing members. Sar ready for paint.	all ds	SF		

Addr	ess:	1822 S Jefferson Casper (revised)	Unit:	Unit 01			
Locat	ion:	14 - Bsmnt Bathroom	Approx.	. Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	19	Paint & Wallpaper					
136	5560	PREP & PAINT BATHROOM  Remove/cover all hardware and fixtures not to be painted. scrape all loose cracked, peeling blistered surfaces. Clean surfaces with TSP. Fill all holes and cracks. Spot prime wit acrylic latex. Apply top coat of owner's choice of premixed acrylic latex semi-gloss.		1.00	RM		
Trade:	20	Floor Coverings					
137	5930	UNDERLAYMENT AND VINYL SHEET GOODS Install 1/4" underlayment grade plywood using 7d screw sha or cement coated nails, or narrow crown coated staples, 6" center allowing a 1/4" gap at wall. Fill seams with a manufacturer approved filler. Install 070" thick, backed viny sheet goods w/ minimum seams, per manufact. recommendations. Install metal edge strips in openings. Owner's choice of pattern and color.	on	100.00	SF		
Trade:	2	Plumbing					
138	6900	VANITY24" COMPLETE  Install a 24" plywood vanity; including top with backsplash, wash bowl and single lever brass bodied chrome faucet with maximum 1.5 GPM flow rate. Include PVC drain attached to code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops on all supply lines. Seal all penetration through the floor, walls and cabinet for plumbing connections using expanding foam or caulk and cover with chrome eschucion plates. Cabinets must comply with California 93120 (formaldehyde content) or all exposed edgmust be sealed with a low-VOC sealant.	o a	1.00	EA		
139	6930	TUB/SHOWER FAUCET WITH DIVERTER Install a single lever, metal shower diverter with faucet, controls, and shower head set (Glacier Bay Item # 418827 equal) in brushed nickel or prior approved equivalent with 1 year drip-free warranty.		1.00	EA		
140	7010	COMMODEREPLACE Install a 2 piece, close coupled, white, vitreous china, commode with a maximum water usage per flush of 1.6 Gallons. Include white seat, supply pipe, shut-off valve, flap valve and wax seal.	ı	1.00	EA		
Trade:	2	B Electric					
141	7731	LIGHT FIXTUREREPLACE VANITY  Replace light fixture with 2 or 3 bulb vanity light. Include sh and lamps. See General Conditions for specified material.	ade	1.00	EA		
142	7818	FIXTURELIGHT, VENT Install a single bulb light fixture with an exterior ducted vent with damper capable of 60 cfm, controlled by 2 manufacturer-supplied switches, using #14 copper Romex. Fish all wire and repair tear out.	fan	1.00	EA		

Address: 182	22 S Jefferson Casper (revised)	Unit: Unit 01	
Location:	14 - Bsmnt Bathroom	Approx. Wall SF: 0	Ceiling/Floor SF: 0
Spec #	Spec	Quantity Units	Unit Price Total Price
Trade: 23	Electric		

Location Total:

Locat	ion:	15 - Bsmnt Bedroom Ap	prox. Wall SF: 0		Ceiling/Floor SF:	0
s	pec#	Spec	Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry				
143	2415	SHOE MOLDING Install pine shoe molding nailed 2' on center to create the tightest possible seal between the baseboard and floor using finish nails or tee headed brads.	125.00	LF		
144	2866	CREATE EGRESS WINDOW  Remove existing window. Cut foundation wall as needed to allow for the installation of an egress window. Install a vinyl slider, double glazed, window, plumb, level, and caulk to ensure a leak free, water tight, sealed installation. Provide a screen. Replace window casing at interior and exterior. Provide a new window well, cover, and an emergency escape ladder. New window must meet current local building codes.	1.00	EA		
145	2984	VINYL WINDOW-BASEMENT Dispose of basement window unit. Install a vinyl slider window plumb and level, caulk, provide a screen.	1.00	EA		
146	3375	DOORWOOD BIFOLD  Hang a flush, hollow core, wood bifold door including overhead track, all hardware and casing on one side, plumb and centered within the opening for each closet.	2.00	EA		
147	4010	CLOSET POLE Field measure and install 1-1/2" diameter wood closet pole and sockets.	1.00	EA		
148	Custom	REPLACE INSULATION  Replace rigid insulation removed in flood cut, insulate North wall in downstairs hall.	1.00	EA		
Trade:	17	Drywall & Plaster				
149	5270	DRYWALL1/2" Hang, tape and 3 coat finish 1/2" drywall. Apply a 3/8" bead of low VOC drywall adhesive to each framing member and install using drywall screws min. 1 5/8 long, 8"on center. Run boards with long dimension perpendicular to framing members. Sand, texture to match existing, ready for paint.		SF		
Trade:	20	Floor Coverings				
150	5970	CARPET AND PAD Install FHA approved, nylon, plush carpet over a 1/2" medium density rebond pad w/ a minimum of seams. Stretch carpet to eliminate puckers, scallops & ripples. Include tackless strips,	225.00	SF		

Address: 16	322 S Jefferson Casper (revised)	Unit: Unit 01			
Location:	15 - Bsmnt Bedroom	Approx. Wall SF: 0		Ceiling/Floor SF:	0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Γrade: 20	Floor Coverings				
	metal edge strips, and mending tape to cover entire floor including closets. On stairs, fasten carpet and pad at top and bottom of each riser. See General Requirements for specifie carpet.				
Trade: 22	Plumbing				
51 <b>7145</b>	SUMP PUMP COMPLETE Install a 1/3 horse power, submersible sump pump complete with pit, liner, and discharge piping on a separate 15 amp circuit within the eastern most closet floor. Coordinate location of discharge piping with WCDA construction Specialist.	1.00	EA		
Frade: 23	Electric				
<b>7730</b>	LIGHT FIXTUREREPLACE  Replace the existing ceiling mounted light with a new ceiling mounted fixture with at least 2 bulbs, UL approved, with sharor globe and lamps.	3.00 de	EA		
		ι	ocation	Total:	
Location:	16 - Attic	Approx. Wall SF: 0		Ceiling/Floor SF:	0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 16	Conservation				
53 <b>4923</b>	INSULATIONINCREASE TO R-50  Blow in borax treated cellulose or loose lay unfaced fiberglas batts over existing insulation to increase total attic rating to a least R-50.		SF		
		ι	ocation	Total:	
Location:	17 - Garage	Approx. Wall SF: 0		Ceiling/Floor SF:	0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
rade: 1	General Requirements				
54 <b>3216</b>	DOOROVERHEAD DOOR REPLACE  Remove existing overhead garage door, tracks, guide,s mote and drive system. Replace with aluminum sectional over head to be a section of the section of the section of the section of the sec	nd	EA		
	garage door. Install tracks, motor, guides, electric safety eye and drive system at existing opening. Provide 2 remotes controllers. Must meet current local building codes.				
Γrade: 6	and drive system at existing opening. Provide 2 remotes				

Address:	1822 S Jefferson Casper (revised)	Unit:	Unit 01				
Location:	17 - Garage	Approx.	Wall SF: 0		Ceiling/Floor SF:	0	
Spec #	Spec		Quantity	Units	Unit Price	Total Price	
Trade: 6	Concrete & Paving						
	graded & compaceted subgrade. Form and pour 3000 pentrained concrete, 4" thick. Provide #10 welded wire mexpansion joints at 10' intervals, and a broom finish surfithat directs water away from the building. Remove form Price to include removal and proper disposal of existing concrete, if applicable.	iesh, ace					
Trade: 10	Carpentry						
156 3175	DOORENTRY COMPLETE Dispose of existing door and frame. Install a 1-3/4" six-fiberglass door and frame. Include interior and exterior of three 4"x 4" butt hinges, spring metal weatherstripping, a interlocking threshold, 1/4 glass, one entrance and one mortised deadbolt lockset keyed alike. Prime and topco owner's choice of finish.	asing, an	1.00	EA			
Trade: 19	Paint & Wallpaper						
157 <b>5483</b>	REPR CRACKS/HOLES, TEXTURE, PREP & PAINT Repair all cracks with fiberglass drywall tape and comporate Fill holes with spackle or drywall compound. Feather educated and wet sand. Spot prime all unpainted surfaces with all primer. Remove all loose and chipped paint, tape all sea and major cracks with fiberglass mesh joint tape. Masky all surfaces not to be textured to eliminate overspray. Swith a latex paint based medium texture per the manuface recommended procedure. Spot prime and top coat trim, walls, doors & windows with owner's choice of premixed latex. Include any and all closets, doors, rooms, walls, ce and trim.	ges kyd ms cover pray cturer's ceiling, acrylic	400.00	SF			
		Location Total:					
Unit Total for 1822 S Jefferson Casper (revised) , Unit Unit 01:							
	Address Grand Total for 1822 S Jefferson Casper (revised) :						
	Bidder:						